

## Easy Piecing Instructions for On-Point Border Panels



1. Cut out squares of Fabric. Use the Layout as a placement guide. Place **WRONG SIDE** of fabric to **BUMPY** or **FUSIBLE** side of the printed interfacing. **\*MAKE SURE THE FUSIBLE SIDE IS UP!!**

The dotted lines make it easy to know where to put your fabric squares. Cutting doesn't need to be perfect, but each square needs to fit inside the printed square and fit safely in your seam allowance. Please note that the fabric square placed along the edge of the border panel will go past the foundation. This excess will be trimmed after all the sewing is done.\*\*

3. Fold on the **DOTTED** line (fold line), making sure the dots are running right along the fold. Sew a 1/4" seam allowance. Continue this step in one direction on all rows. Notice that the panel folds at an angle during this step.

4. Snip right to the seam line between each square. Press each row in opposite directions- use steam. Turn over and press the right side of the fabric, making sure the seams are laying flat.



2. **PRESS** – not iron – for a few seconds, then lift the iron and place it again, until the entire panel is secured. Steam works well in this step!



5. Fold the row right sides together- notice the intersections naturally nest into each other! Sew with a 1/4" seam allowance. Continue this step going the other direction on all rows. Press the seams to one direction, using steam.

\*\*The reason a full square was placed on the outer edge of the panel is because after you've followed the steps for piecing your panel you will trim 1/4" **PAST** the sewn outer point. (You don't want to cut off that point!) Your panel is now ready for your quilt or borders!

